

Postfix

Technical Datasheet






Whitestar Postfix is a ready to use factory blended, quality assured fast setting concrete designed to be used with all types of wooden, concrete and metal posts.






GENERAL INFORMATION

Whitestar Postfix is a pre-blended ready to use material consisting of specially selected cements, aggregates, sands and additives.







FEATURES

-  Weather resistant plastic packaging
-  Ready to use, just add water
-  Rapid setting in 5–10 mins

APPLICATION

-  Please refer to application instructions detailed on the packaging
-  Recommended for use between temperatures of 5°C and 25°C
-  Do not use when ground is frozen at temperatures below 5°C
-  Typical set time between 5 and 10 mins
-  Typical 28-day strength of 20N/mm²

GUIDANCE FOR USE

-  Dig a hole to the required size for the post.
-  Add water to the prepared hole.
-  Add water to the hole to one third of its depth.
-  Add Postfix evenly around the base of the post.
-  Add additional water to dry powder still visible
-  Adjust the post into position and support appropriately for approximately 10 minutes until secure.

Approximate guide

Post size	Hole Depth (mm)	Hole Width (mm)	Approximate number of bags
75x75mm (3")	600	200	¾ - 1
100x100mm (4")	600	250	1-2
150x150mm (6")	750	300	2
200x200mm (8")	900	400	3

Adjust quantities as needed for non-standard hole shapes or additional requirements.

AVAILABILITY

Whitestar Postfix is supplied in 20kg bags throughout the UK.

STORAGE

Bags should be stored unopened, clear of the ground, in cool dry conditions and protected from excessive draft and all sources of moisture.

HEALTH AND SAFETY

Contact with cement may cause skin, eye and respiratory irritation, severe burns and dermatitis. Always wear suitable personal protective equipment (PPE) and refer to the full Material Safety Data Sheet for further information.

TECHNICAL SUPPORT

For further advice please contact Whitestar Technical Helpline on 0800 161 3715.